



Width: 380\* - 1520 mm  
Height: 450 - 2390 mm

N°	Description	Application range by width	Application range by height	Part No.
1	Gear variable ****	-	450-2390	K1001-***-N03
1a	Constant tilt-turn gear ****	-	370-2360	K1004-***-N03
2	Corner transmission 150x150	480-1280	450-2390	K2001-00-N03
2a	Corner transmission 150x150 security	480-1280	450-2390	K2005-00-N03
3	Corner transmission, integrated slit, left	480-1280	450-2390	K2004-00-L03
	Corner transmission, integrated slit, right	480-1280	450-2390	K2004-00-R03
4	Narrow corner transmission 50x150	380-480	450-2390	K2003-00-N03
		480-680	370-550**	
5	Concealed stay arm connecting plate 1 L=530, 480-680, left/right	480-680	-	K3030-06-L/R03
	Concealed stay arm connecting plate 2 L=650, 600-800, left/right	600-800	-	K3030-07-L/R03
	Concealed stay arm connecting plate 3 L=890, 801-1040, left/right	801-1040	-	K3030-09-L/R03
	Concealed stay arm connecting plate 4 L=1130, 1041-1280, left/right	1041-1280	-	K3030-12-L/R03
5a	Concealed stay arm PVC, 13 mm, 480-800, left/right	480-800	-	A3001-02-L/R03
	Concealed stay arm PVC, 13 mm, 801-1040, left/right	801-1040	-	A3001-03-L/R03
	Concealed stay arm PVC, 13 mm, 1041-1280, left/right	1041-1280	-	A3001-04-L/R03
	Concealed stay arm PVC, 9 mm, 480-800, left/right	480-800	-	A3002-02-L/R03
6	Middle lock L=400, 2 ML	600-1000	600-1000	K4004-04-N03
	Middle lock L=650, 2 ML	850-1250	850-1250	K4004-06-N03
	Middle lock L=720, 2 ML	920-1320	920-1320	K4004-07-N03
	Middle lock L=820, 2 ML	1251-1430	1251-1430	K4004-08-N03
6a	Middle lock L=400, 1MR + 1 ML	600-1000	600-1000	K4008-04-N03
	Middle lock L=650, 1MR + 1 ML	850-1250	850-1250	K4008-06-N03
	Middle lock L=820, 1MR + 1 ML	1251-1430	1251-1430	K4008-08-N03
	Middle lock L=1130, 1MR + 2 ML	-	1251-1730	K4008-11-N03
7	Middle lock extension 480 mm	-	1710-2210	K4005-05-N03
	Middle lock extension 680 mm	-	2211-2390	K4005-07-N03
8	Bottom extension	-	450-800	K4009-00-N03
		-	801-2390	K4002-00-N03
9	Tilt locking plate, right/left	-	-	****
10	Locking plate	-	-	****
10a	Locking plate safety	-	-	****
10b	Tilt locking plate safety	-	-	****
11	Lifting plate	-	751-2390	****
12	Wrong operation safety device with sash lifter	-	751-2390	A7001-00-N03
13	Concealed bottom hinge PVC, 9 mm, left/right	-	-	A5025-09-L/R03
	Concealed bottom hinge PVC, 13 mm, left/right	-	-	A5025-13-L/R03
14	Concealed bottom sash hinge, 9 mm, left/right	-	-	A5027-09-L/R03
	Concealed bottom sash hinge, 13 mm, left/right	-	-	A5027-13-L/R03
15	Extension lock 240 mm	-	-	K4003-02-N03
15a	Extension lock for corner transmission L=480 mm	-	-	K4010-00-N03
16	Locking plate, integrated slit	-	-	****
17	Locking plate for integrated slit (frame part)	-	-	****
18	Balcony catch	-	-	A7046-***-N03
18a	Balcony locking pin	-	-	A7031-00-N00
19	Concealed bottom hinge cover, left/right	-	-	A7141-00-L/R03
20	Concealed hinge packer, 13 mm, left/right	-	-	A7***-13-L/R03
21	Sash turning restrictor	-	-	A7110-00-N03
22	Magnetic balcony catch, frame part	-	-	A7053-00-N03
22a	Magnetic balcony catch, sash part	-	-	A7055-**-N03

\* - with narrow corner transmission  
 \*\* - with offset relative to center  
 \*\*\* - according to displacement axis of sash groove (9 mm, 10 mm, 13 mm, 14 mm)  
 \*\*\*\* - see the section "Profile-dependent elements" of catalogues KOMFORT LINE K-3 or ELITE+  
 \*\*\*\*\* - see the section 2 "Gears" of catalogue KOMFORT LINE K-3

